

MACHINES AND ACCESSORIES - pneumatic accessories

EWO hand tyre inflators



EUROAIR

pic.	code	connector	operating pressure	description
1	EW-151200	lever	0 ÷ 4 bar (cars)	Hand-held tyre inflator designed for inflating tyres with air and nitrogen. Includes a pressure gauge 80 mm (accuracy class 1.0) in a polyethylene cover with double scale (bar, psi). A calibrated version requires recalibration every 2 years (Directive 86/217/EEC). A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: aluminium. Connection: EUROSTANDARD 7.2 plug. Working temp.: from -10°C up to +60°C. * without calibration.
2	EW-151260	clip		
3	EW-151210	double-sided push-on		
1	EW-151201	lever	0 ÷ 12 bar (cars and trucks)	
2	EW-151261	clip		
3	EW-151211	double-sided push-on		
1	EW-151243*	lever	0 ÷ 25 bar (special vehicles, planes)	
3	EW-151253*	double-sided push-on		



**EUROAIR
DIGITAL**

pic.	code	connector	description
1	EW-152201	lever	Hand-held tyre inflator designed for inflating tyres with air and nitrogen. Approved by PTB (National Metrology Institute of Germany). Includes a digital pressure gauge 80 mm (display resolution: every 0.05 bar) in a rubber protection cover. The display turns on automatically when inflating starts. It turns off after 20 seconds of stand-by. A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: aluminium. Display: LCD (digits: 15 mm high). Power supply: lithium battery 3V CR2450. Connection: EUROSTANDARD 7.2 plug. Working press.: up to 12 bar. Working temp.: from -10°C up to +60°C. * without calibration.
2	EW-152261	clip	
3	EW-152211	double-sided push-on	
1	EW-152241*	lever	
2	EW-152271*	clip	
3	EW-152251*	double-sided push-on	