Threaded couplings under shell bracket EN 14420-3 / DIN 2817

MSL coupling with BSP female thread (swivel nut) - continuation of table

Sealing: flat gasket (included, standard polyurethane, for stainless steel PTFE)

Hose inside diameter [inch].	Hose inside diameter [mm].	thread size [inch]	material	index	weight [kg]	drawing
1.3/8"	35	BSP 1.1/2"	brass	GD-MSLB-038-035-MS	0,28	
		BSP 2"	AISI 316 steel	GD-MSLB-050-035-SS	~	
			brass	GD-MSLB-050-035-MS	0,43	
1.1/2"	38	BSP 1.1/2"	galvanised steel	GD-MSLB-038-038-ST	0,30	
			AISI 316 steel	GD-MSLB-038-038-SS	0,26	
			AISI 316 E-CTFE steel	GD-MSLB-038-038-SSE	0,26	
			AISI 316 CF-E-CTFE steel	GD-MSLB-038-038-SSEC	0,26	
			brass	GD-MSLB-038-038-MS	0,28	
		BSP 2"	AISI 316 steel	GD-MSLB-050-038-SS	0,26	
			brass	GD-MSLB-050-038-MS	0,39	
	40	BSP 1.1/2"	AISI 316 steel	GD-MSLB-038-040-SS	0,37	
			brass	GD-MSLB-038-040-MS	0,37	
		BSP 2"	AISI 316 steel	GD-MSLB-050-040-SS	0,52	
			brass	GD-MSLB-050-040-MS	0,47	
1.3/4"	45	BSP 2"	brass	GD-MSLB-050-045-MS	0,45	
2"	50	BSP 2"	galvanised steel	GD-MSLB-050-050-ST	0,58	
			AISI 316 steel	GD-MSLB-050-050-SS	0,44	
			AISI 316 E-CTFE steel	GD-MSLB-050-050-SSE	0,44	
			AISI 316 CF-E-CTFE steel	GD-MSLB-050-050-SSEC	0,44	
			brass	GD-MSLB-050-050-MS	0,45	
		BSP 2.1/2"	AISI 316 steel	GD-MSLB-065-050-SS	0,71	
			brass	GD-MSLB-065-050-MS	0,66	
2.1/2"	63/65	BSP 2.1/2"	AISI 316 steel	GD-MSLB-065-065-SS	0,80	
			AISI 316 E-CTFE steel	GD-MSLB-065-065-SSE	0,80	
			AISI 316 CF-E-CTFE steel	GD-MSLB-065-065-SSEC	0,80	
			brass	GD-MSLB-065-065-MS	0,81	
		BSP 3"	brass	GD-MSLB-080-065-MS	1,15	
3"	75	BSP 3"	galvanised steel	GD-MSLB-080-075-ST	0,91	
			AISI 316 steel	GD-MSLB-080-075-SS	1,03	
			AISI 316 E-CTFE steel	GD-MSLB-080-075-SSE	1,03	
			AISI 316 CF-E-CTFE steel	GD-MSLB-080-075-SSEC	1,03	
			brass	GD-MSLB-080-075-MS	1,11	
	80		brass	GD-MSLB-080-080-MS	1,08	
4"	100	BSP 4"	AISI 316 steel	GD-MSLB-100-100-SS	2,71	
			AISI 316 E-CTFE steel	GD-MSLB-100-100-SSE	2,71	
			AISI 316 CF-E-CTFE steel	GD-MSLB-100-100-SSEC	2,71	
			brass	GD-MSLB-100-100-MS	2,66	



galvanised steel
(GD-MSLB-038-038-ST)



stainless steel AISI 316
(GD-MSLB-038-040-SS)



brass
(GD-MSLB-038-040-MS)

MSLB brass connector with 1" BSP female thread attached to hose TU2116T (PR-TU2116T-25BL) for with an aluminium shell bracket (RS-636025006040, size 25x6).

