SKILLAIR series



LUB lubricator

Size: 100, 200, 300, 400
Tank volume: 50 cm^3 - 100 series
95 cm^3 - 200 series
160 cm^3 - 300 series
800 cm^3 - 400 series
Inlet pressure: Up to 15 bar
Working temp.: Up to +50°C
Connection: 1/4" ÷ 2" BSP female thread
Flow rate: 1500 l/min - 100 series
3700 l/min - 200 series
5500 l/min - 300 series
18000 ÷ 20000 l/min - 400 series
(input pressure 6 bar and Δp = 1 bar)

LUB **100** **STD**

element	series (size)	oil filling method
LUB - lubricator	100 200 300 400	STD - standard version, oil refilling by disassembly of the tank or through the cap CA - automatic refilling, refill only when lubricator is working CD - vacuum refilling, pressure drop inside the tank enables refilling. CAML - automatic refilling with minimum level CDML - vacuum refilling with minimum level

100		200		300		400		connection	oil filling method
code	type	code	type	code	type	code	type		
MW-3281001A	LUB 100 STD	MW-3481001A	LUB 200 STD	MW-4481001A	LUB 300 STD	MW-6181001A	LUB 400 STD	without final plates	STD
MW-3281002A	LUB 100 CA	MW-3481002A	LUB 200 CA	MW-4481002A	LUB 300 CA	MW-6181002A	LUB 400 CA		CA
MW-3281005A	LUB 100 CD	MW-3481005A	LUB 200 CD	MW-4481005A	LUB 300 CD	MW-6181004A	LUB 400 CD		CD
				MW-4481006A	LUB 300 CDML	MW-6181006A	LUB 400 CDML		CDML
				MW-4481007A	LUB 300 CAML	MW-6181007A	LUB 400 CAML		CAML