

Threaded couplings - adaptors type DM

Adapter (socket) with female thread

Sealing: flat gasket (included, standard polyurethane, for stainless steel PTFE)

thread size [inch]	material	index	weight [kg]	drawing
1/4" BSP	AISI 316 steel	RS-700025025120	~	 stainless steel AISI 316 (RS-700100100120)
	brass	-	~	
1/2" BSP	AISI 316 steel	RS-700050050120	~	
	brass	-	~	
3/4" BSP	AISI 316 steel	RS-700075075120	~	
	brass	RS-700075075130	~	
1" BSP	AISI 316 steel	RS-700100100120	~	
	brass	RS-700100100130	~	
1.1/4" BSP	AISI 316 steel	RS-700125125120	~	
	brass	RS-700125125130	~	
1.1/2" BSP	AISI 316 steel	RS-700150150120	~	
	brass	RS-700150150130	~	
2" BSP	AISI 316 steel	RS-700200200120	~	
	brass	RS-700200200130	~	
2.1/2" BSP	AISI 316 steel	RS-700250250120	~	
	brass	RS-700250250130	~	
3" BSP	AISI 316 steel	RS-700300300120	~	
	brass	RS-700300300130	~	
4" BSP	AISI 316 steel	-	~	
	brass	RS-700400400130	~	

Threaded couplings - adaptors type RM

Reduction adapter (reduction socket) with female thread

Sealing: flat gasket (included, standard polyurethane, for stainless steel PTFE)

thread size [inch]		material	index	weight [kg]	drawing
ext.	ext.				
1/2" BSP	3/4" BSP	AISI 316 steel	RS-710050075112	~	 stainless steel AISI 316 (RS-710100125112)
	3/4" BSP	1" BSP	AISI 316 steel	RS-710050100112	
1" BSP		1.1/4" BSP	AISI 316 steel	RS-710075100112	
	1.1/2" BSP	AISI 316 steel	RS-710100125112	~	
		brass	RS-710100150113	~	
	2" BSP	AISI 316 steel	RS-710100150112	~	
		brass	RS-710100200112	~	
	1.1/4" BSP	1.1/2" BSP	AISI 316 steel	RS-710100200113	
brass			RS-710125150112	~	
1.1/2" BSP		2" BSP	brass	RS-710125150113	
	brass		RS-710125200113	~	
	2.1/2" BSP	AISI 316 steel	RS-710150200112	~	
		brass	RS-710150200113	~	
2" BSP	3" BSP	AISI 316 steel	RS-710150250112	~	
		brass	RS-710150250113	~	
2.1/2" BSP		brass	RS-710200250113	~	
	3" BSP	brass	RS-710200300113	~	
3" BSP		4" BSP	AISI 316 steel	RS-710250300112	~
	brass		RS-710250300113	~	
S60x6	2" BSP	brass	RS-710300400113	~	
					 brass (RS-710100125113)